



WIPE NEW[®] BLAST CERAMIC COATING

DESCRIPTION AND USES

Wipe New[®] Blast Ceramic Coating is a fast and easy way to deliver a high gloss, ceramic shine to a vehicles finish. This water shedding, hydrophobic formula helps keep your vehicle cleaner, longer. The quick & easy hose attached application ensures even coverage in minimal time and with little effort.

PRODUCT FEATURES

- Delivers high gloss, slickness and protection
- Hydrophobic coating sheds water and repels dirt
- Coat, rinse & dry – no rubbing or buffing required

PRODUCT

| DESCRIPTION | SKU |
|-------------|--------|
| 24 oz. | 381702 |

PRODUCT APPLICATION

DIRECTIONS

(Read entire directions and warnings prior to use.)

Before using Wipe New Blast Ceramic Coating, wash vehicle and rinse. Do not dry. Be sure vehicle is cool to the touch and do not apply do not apply in direct sunlight. Shake well before use.

Step 1 Rinse – Connect Wipe New Blast Ceramic Coating to your garden hose and turn on water by rotating rear knob forward. Thoroughly rinse vehicle exterior.

Step 2 Coat - With rear knob still on “On” position, turn front knob forward to introduce the ceramic concentrate and coat the entire vehicle surface. Once the vehicle is coated, turn “Off” the ceramic so forward knob is back in the original position and only water is coming out of nozzle.

Step 3 Rinse - With nozzle in the “Rinse” position, spray vehicle until any remaining subs are rinsed away.

Turn off water and dry vehicle with a drying towel. **DO NOT LET COATING DRY ON VEHICLE.**

PHYSICAL PROPERTIES

| | | BLAST CERAMIC COATING |
|--|-------|---|
| Pigment Type | | NA |
| Fill Weight | | 24 oz. |
| Solvents | | None |
| Dry Times at 77°F (25°C) and 50% Relative Humidity | Touch | Apply, Rinse Off, Do not let dry |
| Shelf Life | | 2 years |
| Flash Point | | 201°F |
| Safety Information | | For additional information, see SDS |

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.